

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/045874 A1

(51) International Patent Classification⁷: **H01J 37/08**,
27/02

Gladesville, NSW 2111 (AU). **WILLIAM, Waller, V.**
[AU/AU]; Saintech PTY LTD, Unit 6, 43 College St.,
Gladesville, NSW 2111 (AU).

(21) International Application Number:
PCT/AU2004/001082

(74) Agent: **GARDNER, Darren**; Saintech Pty LTD, Unit 6,
43 College St., Gladesville, NSW 2111 (AU).

(22) International Filing Date: 13 August 2004 (13.08.2004)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003906001 31 October 2003 (31.10.2003) AU

(71) Applicant (*for all designated States except US*): **SAIN-
TECH PTY LTD** [AU/AU]; Unit 6, 43 College St.,
Gladesville, NSW 2111 (AU).


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **WAYNE, Sainty,
G.** [AU/AU]; Saintech PTY LTD, Unit 6, 43 College St.,

[Continued on next page]

(54) Title: ION SOURCE CONTROL SYSTEM



(57) Abstract: A gridless ion source operates from a control system (201) that generates an anode voltage (215) comprising a mains rectified signal such that the anode voltage modulates between a first voltage above a threshold and a second voltage below the threshold. The mains rectified signal is provided by transformer (210) receiving a mains input (211). The output of the transformer (213) is rectified by a bridge rectifier (214). In preferred embodiments, the threshold is an ionization threshold such that the ion current is initiated and extinguished in every cycle.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*